ROAM

The MegaWay Cargo Story



Low-cost, ultralight electrified Superway along highway ROW

Initial manual control train service

120-mph MegaWay removes most pavement-busting, heavy box trucks from highways, speeds commerce & cuts costly truck terminal operations

ROAM™ Transport Systems, Fort Worth, Texas

SuperWay, MegaWay, CargoWay, MicroWay, CarLiner, CarFerry, SkyCoach, CargoLiner, WhisperLiner, MegaLiner, & PersonLiner are trademarks of ROAM Transport Systems
U.S. PATS. 6,039,135, 6,401.625, 6,435,100. 6,615,740, 6,742,458, 6,834,595, 6,837,167,& 7,926,425 B2
OTHER U.S. & INTERNATIONAL PATENTS PENDING

ROAM graphics & photos

® Reg. U.S. Pat. & Tm. Off.

Heavy Truck Highway Impacts

- 80,000-lbs plus weight Over two tons per tire
 - Concentrate load on small areas breaking pavement
 - Ruts in asphalt pavement in hot weather
 - Even small tire balance problems hammer pavement
 - Heavy stress shortens bridge beam & connector life
- Truck collisions can destroy bridge columns
- Major factor in congestion & accidents
 - Large stopping distances & slow acceleration
 - Easy to jackknife on slick pavement Hours to reopen roads

Single truck – more damage than 1,000 cars

MegaWay Moves All Box Truck Cargo

- Cargo in boxes, barrels, crates, bags, etc.
- Most cargo moved on standard shipping pallets
 - Often fully wrapped with plastic wrapping
- Most cargo pallets & crates forklift compatible
- Typically loaded into truck trailers with forklifts
- Plus MegaWay offers refrigerated containers

Truck average speed – 55 to 60-mph

120-mph MegaWay Container Trains




Non-stop terminal to terminal service

Transport most heavy box truck cargo Inhitial manually-controlled trains

Cuts Truck Traffic, Pavement Damage, Pollution & Noise


Later Automated MegaWay Carriers



Each standard container = 1-1/2-tons for 3 tons total

(Non-stop terminal to terminal transport)


Empty MegaWay Carrier is Low Drag



End Caps Fold for Minimum Drag

Major reduction in energy use


MegaWay Carrier with Large Container



Large, 3-ton High-speed Cargo Container on SuperWay (Longer container for longer cargo)

7 RMWCRG-CAP-6


Standard MegaWay Cargo Container



One & one-half-tons per container


Refrigerated units have power contacts on bottom

Side Loading Container



Standard *MegaWay* Cargo Container

Side view with doors open




Reduces Costly Terminal Cargo Transfers

- Much of cargo transferred inside containers
- Reduces terminal handling of pallets, etc.
 - Cargo remains in small containers for terminal transfers
- MegaWay cargo containers forklift compatible
- Many containers move directly to destination

Lower terminal operating costs

MegaWay Containers Handled by Forklift

Carrier loading with overhead lifts




Loaded or Empty Containers Easy to Move on Dock

Full Compatibly with Trucking Operations

- All cargo moved inside closed containers
- Easy transfer between MegaWay and trucks
 - Easy shift of containers between modes at terminals
- MegaWay cargo containers forklift compatible
- Containers compatible with short & long flatbeds


Standard *MegaWay* Containers on Truck



Containers moved on trucks for road transport


Standard containers – 1-1/2-ton capacity each

Large-size MegaWay Cargo Container



Three-Ton Capacity per Container


Easy Load/Unload Large-size Containers



Cargo Pallet Load/Unload by Standard Forklifts

Forklifts drive into & out of containers

Large-size Container on Truck



Containers moved on trucks for local transport

Loaded/unloaded by standard forklifts

Cargo Carriers Designed for Low Cost

Lightweight Design & Ease of Maintenance

- Systems in lower chassis unit for access ease
- All metal parts cut by robot plasma & laser cutters
- Most raw material is flat stainless-steel
- Entire structure of welded stainless sheet
- Empty carrier weight 1,200 pounds
- Low complexity control systems

Carriers are light weight & low cost

MegaWay High-speed **Cargo** Capacity Greater Capacity than a Six Lane Freeway

- Cargo moves at 120-mph speed Not 55-mph!
- No traffic jams or delays 24 hours per day
- Max cargo capacity calculation: (per direction)
 - Carriers spaced at 50-ft intervals = 105 vehicles/mi
 - 105 containers/mi x 120-mph x 3-tons = 37,800 tons/hr
 - 37,800 tons/hr x 24-hrs = 907,000 tons/day = 22,000 trucks
- Plenty of space for high-speed passenger service

Plus the freeways remain available!

SuperWay Shared by Cargo & Passengers



Cargo moves in closed containers with low-drag fairings


20 RMWCRG-CAP-6

Future High-speed, Inter-city Services 6,435,100 U.S. Patent 6,615,740 MegaRail p


U.S. Pat. 6,435,100



Carferries carry standard cars with driver and passengers inside



Automated, eight to nine-passenger MegaLiner™ non-stop,120-mph, high-frequency, 24-hr group service



Automated cargo car on SuperWay moves modules at speeds up to 120-mph



Four to six-passenger *PersonLiner*™ non-stop,120-mph, on-call, 24-hr personal service

21 **RMWCRG-CAP-6**

Ultimate Cargo & Passenger Service

- Cargo and passengers Non-stop at 120-mph!
- More capacity than costly, new 6-lane tollways
- Ultra smooth cargo and passenger ride
- Reduced, all-electric power Less air pollution!
- No need for costly high-speed rail + shorter trips
- Noise-free & minimum environment impact!

Average trip speed – 120-mph



401 West Jim Wright Freeway, Suite113

Mail Address
P. O. Box 121728
Fort Worth, Texas 76121

(817) 738-9507

FAX (817) 367-2373

contact@roamtrans.com

www.roamtrans.com

Revolutionary, High-speed, Multi-user 21st Century Transport!

- Unprecedented level of service
- Low transportation user costs

Near-term & affordable solution to traffic & air pollution problems